




Tubular Motor

MM-45R



Ø 45

Diameter 45mm



|Mechanical Limit Switch



|Build-In Receiver

|Precise Setting of Limit Positions

|5-Year Warranty

|Stable Performance

|Low Noise

|Easy To Install



Technical Data

Model	Torque	Speed	Voltage	Frequency	Power	Current	Degree of Protection	Running Time
MM45R-10/15	10N.m	15rpm	230V/120V	50Hz/60Hz	130W	0.6A	IP44	4min
MM45R-20/15	20N.m	15rpm	230V/120V	50Hz/60Hz	130 W	0.6A	IP44	4min
MM45R-20/26	20N.m	26rpm	230V/120V	50Hz/60Hz	205W	0.9A	IP44	4min
MM45R-30/15	30N.m	15rpm	230V/120V	50Hz/60Hz	240W	1A	IP44	4min
MM45R-40/12	40N.m	12rpm	230V/120V	50Hz/60Hz	255W	1.1A	IP44	4min
MM45R-40/15	40N.m	15rpm	230V/120V	50Hz/60Hz	285W	1.2A	IP44	4min
MM45R-50/12	50N.m	12rpm	230V/120V	50Hz/60Hz	275W	1.2A	IP44	4min
MM45R-50/15	50N.m	15rpm	230V/120V	50Hz/60Hz	310W	1.3A	IP44	4min
MM45R-60/10	60N.m	10rpm	230V/120V	50Hz/60Hz	285W	1.2A	IP44	4min
MM45R-60/12	60N.m	12rpm	230V/120V	50Hz/60Hz	315W	1.4A	IP44	4min
MM45R-60/15	60N/m	15rpm	230V/120V	50Hz/60Hz	325W	1.4A	IP44	4min
MM45R-60/18	60N/m	18rpm	230V/120V	50Hz/60Hz	345W	1.5A	IP44	4min
MM45R-70/9	70N.m	9rpm	230V/120V	50Hz/60Hz	295W	1.3A	IP44	4min